

Toxic Substances Safety Cabinet

New from Pratt! Safety Cabinets which comply with the latest Australian Standard "The Storage & Handling Of Toxic Substances" AS/NZS 4452:1997. The Pratt Toxic Substances Safety Cabinet has all the features required by Australian Standards plus added benefits you have come to expect from Pratt which enhance your safety culture. Pratt Safety Cabinets for toxic substances are available through Pratt Distributors



PRATT SAFETY CABINETS TECHNICAL DATA

Part No.	Capacity Based On PG III	Number Of Shelves	Extra Shelf Part No.	External Height mm	External Width mm	External Depth mm	Internal Height mm	Internal Width mm	Internal Depth mm
5516AST	30L	1	5517T-29	800	505	460	520	420	375
5517AST	60L	2	5517T-29	1065	505	460	785	420	375
5535AST	100L	1	5535T-29	800	920	615	520	835	530
5530AST	160L	2	5545T-29	1295	1100	460	1015	1015	375
5545AST	250L	3	5545T-29	1825	1100	500	1545	1015	420
5560AST	250L	3	5560T-29	1825	1430	580	1545	1345	495

Cabinet parts and accessories

• Additional shelves and trays are available. Please see part numbers listed in this brochure. • Replacement hydraulic door closer, part number 277A-125-300. • Replacement door spring, part number 5560-IIA-300. • Replacement door handle assembly, part number 5545-20-300. • Shelf bracket extensions (set of 5) for flammables cabinets, part number 738026. This enables previous design of cabinet to be fitted with a shelf directly over the sump where required by regulation. Order bracket extension set plus appropriate additional shelf. • Shelf bracket extension set for corrosive substances cabinets, part number 738027. Order bracket extension set plus appropriate additional shelf, if required.

Additional sample of Pratt products



Full range of safety cans for a variety of applications including storage, dispensing and disposal of flammable liquids.



Model No	
7955L	Drum trolley and lever
506G	Self closing safety faucet
B5706	Hose extension
5522	Safety drum vent
1322	Drip can
2660HL, etc	Grounding wire assembly
249DF8	Safety can
Note:	May be used with model 5555S cabinet

Spill Containment Products

Comply with EPA requirements, avoid costly clean-ups and fines, reduce waste and keep your employees safe.



Drum Dispensing Spill Dolly

Transports a 205L (55gal) drum with ease and tilts to become a dispensing station. Also acts as a secondary containment unit with 302L (80gal) sump capacity. Made of tough, durable and corrosion-resistant polyethylene. Light weight design of only 43kg (95lb) for ease of handling. Moulded grip handles, kick plate and secure strap make tipping to horizontal dispensing position a one-man operation. Supplied with 254mm (10") polyolefin wheels.

Optional Wheel Conversion Kit comes with everything you need to convert your dolly into an all-terrain model with 254mm (10") pneumatic rubber wheels, ideal for outdoor use.

No.	Description	Capacity	UDL	H	W	L	Regulations
72104	Dolly w/254mm (10") Poly Wheels	302L (80gal)	273kg (600lb)	686mm (27")	838mm (33")	1753mm (69")	EPA 40 CFR 264.175
72110	Wheel Conversion Kit						



Spill Trolley

Provides secondary containment for incidental spills and drips that often occur during vertical dispensing operations. Spills are contained in the well, which is fitted with a drain plug for ease of emptying. Metal T-handle sold separately.

No.	Description	Capacity	UDL	H	W	L	Regulations
72202	Spill Trolley	42L (11gal)	227kg (500lb)	229mm (9")	889mm (35")	889mm (35")	
72204	Metal T - Handle				254mm (10")	940mm (37")	



Spill Trays

Provide temporary protection against incidental drips or spills from pails, or drums up to 205L (55gal). Made of tough 100% polyethylene, will not rust or corrode.

No.	Description	Capacity	UDL	H	W	L	Regulations
72220	Pail Spill Tray	26L (7gal)		190mm (7 1/2")	559mm (22")	559mm (22")	
72218	1 - Drum Spill Tray	72L (19gal)		190mm (7 1/2")	863mm (34")	863mm (34")	

Spill Containment Pallets

Protect employees and prevent costly cleanups by keeping overflows and spills off the floor. These secondary containment units are engineered to meet the rigors of today's stringent environmental regulations, exceeding EPA requirements. 100% polyethylene construction provides excellent chemical resistance. New and improved non-skid, removable structural-foam grates. All pallets provided with drain hole and plug, for easy recovery of spilled liquid.



2 Drum
No. 72428

- > 432mm (17") high profile
- > Maximum sump - 219L (58gal)
- > UDL weight - 909kg (2000lb)
- > Forkliftable from two sides
- > Optional Ramp w/ Extender
Nos. 72508 & 72508-60



4 Drum, Low Profile, In Line
No. 72412

- > 305mm (12") high profile
- > Maximum sump - 249L (66gal)
- > UDL weight - 1364kg (3000lb)
- > Raised edge on back and sides stabilizes drums when loading.
- > Shown with ramp, No 72508



4 Drum, Low Profile, Heavy Load
No. 72432

- > 305mm (12") high profile
- > Maximum sump - 249L (66gal)
- > UDL weight - 2727kg (6000lb)
- > Forkliftable from four sides
- > Optional Ramp, No. 72508

No.	Description	Capacity	UDL	H	W	L	Regulations
72428	2 Drum	219L (58gal)	909kg (2000lb)	432mm (17")	737mm (29")	1372mm (54")	EPA 40 CFR 264.175
72412	4 Drum, Low Profile In Line	249L (66gal)	1364kg (3000lb)	305mm (12")	635mm (25")	2489mm (98")	EPA 40 CFR 264.175
72432	4 Drum, Low Profile Heavy Load	249L (66gal)	2727kg (6000lb)	305mm (12")	1372mm (54")	1372mm (54")	EPA 40 CFR 264.175

Containment Pallet Accessories

Combine with any square containment pallet for efficient drum stacking. Can also be used directly on floor if containment sump is not required. Two multi-function drum racks can be stacked to accommodate 4 drums where space is limited. Pallet sold separately.



Multi-Function Drum Rack
No. 72215



Poly Ramp
No. 72508

Ramp Extender
No. 72508

No.	Description	Capacity	UDL	H	W	L	Regulations
72215	Multi Function Drum Rack		1091kg (2400lb)	508mm (20")	1041mm (41")	1245mm (49")	
72508	Poly Ramp		454kg (1000lb)	330mm (13")	787mm (31")	1702mm (67")	
72508-60	Ramp Extender		454kg (1000lb)	178mm (7")	229mm (9")	762mm (30")	



Racking/Stacking Drum System

Unique dispensing and storage system that starts with the Racking Base No. 72210, a one-piece polyethylene unit that holds two 205L (55gal) drums securely, providing 378L (100gal) plus secondary containment. Deep dispensing wells make it easy to fill 20L (5gal) containers. A drain plug is located on each side for convenience.



By adding No. 72212, Racking / Stacking Rack, you can stack two additional 205L (55gal) drums on top of the base unit quickly and easily by forklift. By adding another level you are now easily storing six 205L drums. The entire unit can be transported by forklift. No. 72214, racking /stacking shelf allows for easy dispensing at any level. A hole in the bottom allows for any spills to be drained into the dispensing well of the base unit.

Note: Do not use plastic drums at load bearing level.

No.	Description	Capacity	UDL	H	W	L	Regulations
72210	Racking Base	385L (102gal)	1364kg (3000lb)	584mm (23")	1346mm (53")	1245mm (49")	EPA 40 CFR 264.175
72212	Racking/Stacking Rack		1091kg (2400lb)	330mm (13")	1041mm (41")	1245mm (49")	EPA 40 CFR 264.175
72217	Single Base	249L (66gal)	727kg (1600lb)	813mm (32")	1346mm (53")	787mm (31")	EPA 40 CFR 264.175
72213	Single Rack		364kg (800lb)	508mm (20")	1041mm (41")	787mm (31")	
72214	Shelf		27kg (60lb)	457mm (18")	559mm (22")	432mm (17")	

2, 4, 6 & 8 – Multiple Drum Work Centres

Each work center is designed for stand alone use or may be combined with other work centres for a customized work area, optimizing space for increased safety and efficiency. 100% polyethylene constructed. Large sump capacity for any incidental spills and removable grates for easy cleaning.

Note: Work Centres are not designed to be transported by forklift. See Spill Containment Pallets.



No.	Description	Capacity	UDL	H	W	L	Regulations
72424	2 Drum	83L (22gal)	1090kg (2400lb)	152mm (6")	736mm (29")	1346mm (53")	
72422	4 Drum	163L (43gal)	2727kg (6000lb)	152mm (6")	1346mm (53")	1346mm (53")	
72420	6 Drum	230L (61gal)	3182kg (7000lb)	152mm (6")	1346mm (53")	1956mm (77")	EPA 40 CFR 264.175
72414	8 Drum	291L (77gal)	3636kg (8000lb)	152mm (6")	1346mm (53")	2540mm (100")	EPA 40 CFR 264.175
72418	Locks (Set of 2)			89mm (3 1/2")	178mm (7")	241mm (9 1/2")	
72416	Work Ramp		454kg (1000lb)	152mm (6")	1219mm (48")	660mm (26")	



Polly Drum Funnel

Convenient poly funnel drains liquids from multiple oil filters, pails, containers, etc., simultaneously. Light weight and easy to clean. Fits both open-head and closed-head drums. Optional cover is lockable. (Lock not included).

No.	Description	Fits Drum	Internal		External	
			Dia.	H	Dia.	H
72730	Drum Funnel	205L (55gal)	559mm (22")	102mm (4")	660mm (26")	140mm (5 1/2")
72734	Cover					



Lab Spill Tray

Large surface and low profile makes this ideal for use at the laboratory bench. Removable grate for easy cleaning. Also perfect for workshop, factory and general industrial applications. Polyethylene construction – no metal parts to rust or corrode.

No.	Description	Capacity	UDL	H	W	L	Regulations
72804	Lab Spill Tray	9L (2 1/2gal)	18kg (40lb)	76mm (3")	559mm (22")	635mm (25")	EPA 40 CFR 264.175

Overpack Salvage Drums

Meet or exceed performance-oriented packaging requirements of UN and DOT Regulations. UV-protected polyethylene construction provides excellent chemical and corrosion resistance. The twist-down lid incorporates a closed-cell gasket to maintain a tight closure seal. Patented castellations in the lid allows for easy closing with a pole or two-by-four. Patented ribbed / moulded design provides extra strength and allows for easy gripping and pick-up by material handling equipment. Light weight and nestable for efficient storage. Model 72020 is ideal for containment and disposal of leaking 205L (55gal) drum. Model 72222 is perfect for disposal of laboratory or medical waste. Also ideal as a spill response kit container. Both drums incinerate completely.



No.	Description	Capacity	UDL	Internal			External			Regulations
				Top Dia.	Bottom Dia.	H	Top Dia.	Bottom Dia.	H	
72020	Overpack Salvage Drum	360L (95gal)	295kg (650lb)	686mm (27")	629mm (24 3/4")	940mm (37")	787mm (31")	660mm (26")	1067mm (42")	UN 1H2/X295/S UN 1H2/Y318/S DOT 49 CFR 173.3(c)
72222	Overpack Salvage Drum	76L (20gal)	75kg (166lb)	546mm (21 1/2")	432mm (17")	445mm (17 1/2")	584mm (23")	457mm (18")	483mm (19")	UN 1H2/x75/5 CFR 173.3