




"A" Style Ground Tent

single zipper door w/ tie-backs

"A" Model Tents include two screen windows with roll up flaps, three tie down cords through the hub, ground flaps, single zippered front door, exterior roof line loops for tie down, carry case and three tent stakes.



"D" Style Ground Tent

interconnectable door flap

"D" Model tents include two screen windows with roll up flaps, three tie down cords through the hub, ground flaps, heavy duty frame, wide open front, snap and D-rings with interconnectable flaps (connect 2 tents together), ventilation hose entry sleeve, interior and exterior roof line loops for tie down, carry case and three tent stakes.



"Z" Style Ground Tent

dual zipper roll up door

"Z" Model tents include two screen windows with roll up flaps, three tie down cords through the hub, ground flaps, heavy duty frame, wide open front, dual zipper roll up door, ventilation hose entry sleeve, interior and exterior roof line loops for tie down, carry case and three tent stakes.



Tents Feature:

- One-piece, instant set up
- No loose parts
- Two screened windows
- Tie-down cords through hubs
- Ground flaps for weight anchoring
- Rubber, non-slip feet
- Exterior, roof level D-rings
- Carry case & tent stakes



One-piece instant shelters set up as easy as 1 - 2 - 3!



Model	Size	Weight	Folded Dimension
6504A	48" x 48" (122 x 122 cm)	18 lbs (8.2 kg)	6" x 46" (15 x 117 cm)
6506A	70" x 70" (178 x 178 cm)	20 lbs (9.1 kg)	6" x 56" (15 x 142 cm)
6508A	94" x 94" (239 x 239 cm)	31 lbs (14.1 kg)	7" x 66" (18 x 168 cm)
6510A	118" x 118" (299 x 299 cm)	34 lbs (15.4 kg)	8" x 76" (20 x 193 cm)
6514A	166" x 166" (422 x 422 cm)	162 lbs (73.5 kg)	10" x 124" (25 x 315 cm)

Model	Size	Weight	Folded Dimensions
6506Z	70" x 70" (178 x 178 cm)	21 lbs (9.5 kg)	6" x 56" (15 x 142 cm)
6508Z	94" x 94" (239 x 239 cm)	32 lbs (14.5 kg)	7" x 66" (18 x 168 cm)
6510Z	118" x 118" (299 x 299 cm)	34 lbs (15.4 kg)	8" x 76" (20 x 193 cm)
6512Z	142" x 142" (360 x 360 cm)	92 lbs (41.7 kg)	10" x 100" (25 x 254 cm)

Model	Size	Weight	Folded Dimensions
6506D	70" x 70" (178 x 178 cm)	21 lbs (9.5 kg)	6" x 56" (15 x 142 cm)
6508D	94" x 94" (239 x 239 cm)	32 lbs (14.5 kg)	7" x 66" (18 x 168 cm)
6510D	118" x 118" (299 x 299 cm)	36 lbs (16.3 kg)	8" x 81" (20 x 205 cm)
6510C	118" x 118" (299 x 299 cm)	51 lbs (23.1 kg)	8" x 88" (20 x 223 cm)
6512D	142" x 142" (360 x 360 cm)	94 lbs (42.6 kg)	10" x 100" (25 x 254 cm)

Special Tents & Shelters



"DRAD" Ground Tent

D style w/rear access door

This tent incorporates the standard features found in the "D" series ground tents, along with a 30" wide rollup rear door for personnel entry and exit. It is ideal for working up against any type of cabinet. The tent also doubles as a stand alone ground tent for construction or splicing. Two sizes available: **Model 6508DRAD and 6510DRAD.**

"High-5" Ground Tent

D style w/extra height

Tent measures 6' X 6' X 8' high. Ideal for use over industrial tripod or davit retrieval hoists. May be used to cover pad or pole mounted cabinets or anywhere that additional height is required. Rear Access 1/2 moon style zipper door included. Door style velcro slit and 8" dia. heater/ventilator hose sleeve. **Model 65068A.**



Ground Tent w/Cable Slot

D style w/cable slot access door

This "D" Model ground tent features a vertical slit in the rear wall, from the hub to the ground. Slit is closed over by means of a "Velcro" style closure and a hook & ring assembly. Used to allow entry of cable or pipe when doing fusion or splicing in the tent. Includes vent sleeve. Two sizes available: **Model 6506DCS and 6508DCS.**

Model	Size	Weight	Folded Dimension
6508DRAD	8' x 8' x 6' H (243 x 243 x 183 cm)	32 lb (14.5 kg)	7" x 7" x 66" (18 x 18 x 168 cm)
6510DRAD	10' x 10' x 6.5' H (305 x 305 x 198 cm)	36 lb (16.3 kg)	8" x 8" x 81" (20 x 20 x 205 cm)
65068A	6' x 6' x 8' H (178 x 178 x 244 cm)	27 lbs (12.2 kg)	7" x 7" x 66" (18 x 18 x 169 cm)
6506DCS	6' x 6' x 6' H (183 x 183 x 183 cm)	21 lb (9.5 kg)	6" x 6" x 36" (15 x 15 x 117 cm)
6508DCS	8' x 8' x 6' H (243 x 243 x 183 cm)	32 lb (14.5 kg)	7" x 7" x 66" (18 x 18 x 168 cm)
6508LG	8' x 8' x 6' H (243 x 243 x 183 cm)	38 lb (17.2 kg)	12" x 12" x 70" (30 x 30 x 179 cm)
6508LGF	8' x 8' x 6' H (243 x 243 x 183 cm)	41 lb (18.6 kg)	12" x 12" x 70" (30 x 30 x 179 cm)
6508LGH	8' x 8' x 6' H (243 x 243 x 183 cm)	47 lb (21.3 kg)	12" x 12" x 70" (30 x 30 x 179 cm)
6508DES	8' x 8' x 6.5' H (243 x 243 x 198 cm)	32 lb (14.5 kg)	7" x 7" x 66" (18 x 18 x 168 cm)
6510DES	10' x 10' x 6.5' H (305 x 305 x 198 cm)	36 lb (16.3 kg)	8" x 8" x 81" (20 x 20 x 205 cm)

Fiber Optic Splicing Tents

This Innovation features a heavier polycotton breathable fabric and solar fly/sunshade. The walls are solid white and constructed of acrylic for "breathability" and increased light. Cable slots w/ "velcro" style closures allow easy access to cable while doors are shut. May be used with Pelsue portable air conditioners and heaters.

6508LG Fiber optic splice tent with solar fly, no floor.

6508LGF Fiber optic splice tent with solar fly and standard floor.

6508LGH Fiber optic splice tent with solar fly and heavy duty floor.



Emergency Use Tents

Emergency Response tents feature highly visible lime green fabric & a reflective stripe. Perfect for Fire & Police Departments, Ambulance Crews, Bio-Terror Incidents, Hazmat Decontamination, Mass Casualty Incidents, Rehab Situations, Command Post, Patient Isolation, Emergency Response, and Fire/Rescue Operations. Anywhere, anytime instant shelter is needed, these tents can be set up in seconds. Custom color, size, and logos available!

6508DES Ground tent, lime green & white w/reflective stripe

6510DES Ground tent, lime green & white w/reflective stripe

Decon Shelter Systems available to fit a wide variety of needs. (call for details)

Shelter Heating, A/C Kits also available. Propane heater, ventilator, 15' ventilator hose, plastic hose canister, and LPG hose. Air Conditioners in 13,500 (120 VAC) or 24,000 (220 VAC) models.



Multi Use Tents

Approved & Accredited by
WorkSafeGEAR[®].com
A Division of Heigtech Safety Systems



Multi Tent - Model 6334A



The 5-in-1 specialty tent is a single tent which, when used with the appropriate hardware, can perform multiple functions. The tent may be attached to a manhole guard, pole, ladder, strand, or bucket truck. Door style features snap & D-ring closures. Includes strand mounting hardware (P/N 63350). All other hardware ordered separately. Available in two models:


Model 6334A

44" x 44" x 90"H (112 x 112 x 228H cm) Weight 11 lbs (5 kg)
 Folded Dimensions 6" x 6" x 35" (15 x 15 x 89 cm)

Model 6334AN

59" x 59" x 90"H (150 x 150 x 228H cm) Weight 18 lbs (8.2 kg)
 Folded Dimensions 6" x 6" x 46" (15 x 15 x 117 cm)

Note: when ordering hardware for this model, add "AN" to the end of hardware part number (for example: guard hdwr = 63390AN).



Bucket Hardware
model 63360



Strand Hardware
model 63350



Guard Hardware
model 63390



Ladder/Pole Hdw
model 63380



Trench Tents

Available in three standard sizes, these tents offer protection from the elements during trenching or boring operations. One piece construction allows for easy set up and dismantle. Openings on both ends for easy access. One-piece structure features no interior obstructions. This tent may be used as a modular setup by adding as many units (end-to-end) as required.

Model 6408A

Dimensions 8' x 16' x 6.6'H (2.4 x 4.9 x 2.0H m)
 Weight 43 lbs (19.5 kg)
 Folded Dimensions 8" x 8" x 75" (20 x 20 x 190 cm)

Model 6413A

Dimensions 13' x 24' x 8.25'H (3.9 x 7.3 x 2.5H m)
 Weight 109 lbs (49.5 kg)
 Folded Dimensions 12" x 16" x 100" (30.5 x 41 x 254 cm)

Model 6416A

Dimensions
 16' x 30' x 10.25'H
 (4.9 x 9.1 x 3.1H m)
 Weight 185 lbs (83.9 kg)
 Folded Dimensions
 12" x 16" x 129"
 (30.5 x 41 x 328 cm)



Manhole Tents

Manhole tent models 6000 and 6005 are built to fit most manhole guards on the market today having an inside pipe diameter of 3/4" (19 mm). Model 6000 includes a bowed metal frame, and fits guards with four vertical post openings. Model 6005 has a fiberglass frame and fits guards which have only the two front vertical pipes to attach to. Standard color is yellow.

Model 6000

For use w/Pelsue Guard # 4000
 Dimensions 40" x 40" x 66" H
 (102 x 102 x 168H cm)
 Weight 8 lbs (3.6 kg)
 Folded Dimensions 6" x 6" x 38"
 (15 x 15 x 96 cm)

Model 6005

For use w/Pelsue Guard # 4000A
 Dimensions 40" x 40" x 66" H
 (102 x 102 x 168H cm)
 Weight 6 lbs (2.7 kg)
 Folded Dimensions 6" x 6" x 38"
 (15 x 15 x 96 cm)



Cabinet Tents & Shelters



Cabinet Mounted Canopies - CM Series



A light weight, one piece canopy is attached to a cabinet or vehicle using an aluminum extruded track assembly. The track is applied to the cabinet or vehicle by a peel and stick "3M" adhesive tape which is permanent. Once the track is in place, the canopy may be installed and dismantled within seconds. Adjustable aluminum legs at the front allow for multiple cabinet heights. Has optional sidewalls which are secured to the canopy by a "Velcro" style closure. Fabric: white polyester.

CM Series Track System

The tracks used in the CM series tents & canopies are extruded aluminum and come with a "3M Brand -VHB" adhesive backing. This is a permanent bond adhesive and appropriate care should be taken during installation. Tracks must be installed on a clean, dry surface, and at an ambient temperature of no less than 50 degrees F, or 10 degrees C. Weight: 36" = 1 lb (.914M = 45g)

Order in 1-inch increments in lengths of 28" - 115".
Use model # CMT + 000 + length in inches. (for example: 48" = CMT 000 48)

* Note: Custom canopies available - call for details.

Also available: "CM" Series Cabinet Mounted Tents (same as above but w/hub & rod assembly side walls). Special Track Kits and Custom Built Tents available to fit a wide variety of cabinets.



Work Umbrella

Universal style work umbrella. Sturdy PVC fabric (yellow), with wood mast.

Model 6772

72" diameter work umbrella, yellow.

NFPA Lifeline

Approved & Accredited by
WorkSafeGEAR[®].com
A Division of HeighTech Safety Systems



NFPA Lifeline Safety Rope

Our Lifeline is a product of over 20 years of development. Experience, field-testing and design research has made our Lifeline the highest quality and best performing rescue ropes anywhere. Our Lifeline Safety Ropes are specifically designed for raising and lowering human life under the most severe conditions. Our thicker 16-strand sheath provides durability, resistance to abrasion as well as exceptional gripping power. Features excellent handling characteristics: balanced between enough stiffness for rappelling yet pliable enough for easy handling.

Smaller diameter rope is designed to be used for personal escape and safety lines. Larger diameter rope is designed to be used for Heavy Duty Search & Rescue, Fire Rescue, Mountain Rescue, Industrial Rescue, Rappelling, Litter Hauling, Confined Space Entry, Police Tactical Situations, and Military Operations.



Model	Dia.	Color	MBS lbs.(kN)	NFPA Rating	Approx. Wt. (lbs./100')
PR375N-OW600	3/8" (9.5mm)	Orange w/ White Tracer	5,625 (25 kN)	1 Person (lite use)	4.9
PR437N-BW600	7/16" (11mm)	Blue w/ White Tracer	6,800 (30 kN)	1 Person (lite use)	6.4
PR437N-KK600	7/16" (11mm)	Solid Black	6,800 (30 kN)	1 Person (lite use)	6.4
PR437N-OW600	7/16" (11mm)	Orange w/ White Tracer	6,800 (30 kN)	1 Person (lite use)	6.4
PR437N-WO600	7/16" (11mm)	White w/ Orange Tracer	6,800 (30 kN)	1 Person (lite use)	6.4
PR500N-BW600	1/2" (13mm)	Blue w/ White Tracer	9,450 (42 kN)	2 Person (general use)	8.7
PR500N-KK600	1/2" (13mm)	Solid Black	9,450 (42 kN)	2 Person (general use)	8.7
PR500N-OB600	1/2" (13mm)	Orange w/ Blue Refl. Tracer*	9,450 (42 kN)	2 Person (general use)	8.7
PR500N-OW600	1/2" (13mm)	Orange w/ White Tracer	9,450 (42 kN)	2 Person (general use)	8.7
PR500N-RW600	1/2" (13mm)	Red w/ White Tracer	9,450 (42 kN)	2 Person (general use)	8.7
PR500N-WO600	1/2" (13mm)	White w/ Orange Tracer	9,450 (42 kN)	2 Person (general use)	8.7
PR625N-OW	5/8" (16mm)	Orange w/ White Tracer	11,250 (50 kN)	2 Person (general use)	12.4

* Denotes Lifeline with Reflective Strand. Great for Confined Spaces.

- 600' spools Standard (1200' special request)
- Certification: Meets UL Third Party Testing Classified to NFPA 1983-2001 edition standards.
- Construction: Static Kernmantle, 16-Carrier Braided Nylon Sheath over a Block Creel Continuous Filament Nylon Core. 100% Nylon Material. Melting Temperature: 450°F
- Sheath: 16-Carrier Torque Balanced, Braided Jacket with S-Z Twist - half of the strands have a right twist (S) half of the strands have a left twist (Z)
- Labeling: Internal labeling includes: Date of Mfg, Lot#, Type of Material, Mfg, Name, and Standard to meet NFPA 1983-01 ed.